


Base from U.S. Geological Survey Howard Pass B-2, 1984, Quadrangle, Alaska




DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Sinterex cesium magnetometer. The EM and magnetic sensors were flown at a height of 100 feet. In addition to the survey recorded data from a radar altimeter, GPS navigation system, 50/60 Hz monitors and video camera. Flights were performed with an AS350B-3 Squirrel helicopter at a mean terrain clearance of 200 feet along NN-SE (340°) survey flight lines west of the red line shown on the location index and NE-SW (25°) survey flight lines east of the red line. Flight lines were spaced a quarter of a mile with the exception of the Drenchwater Creek area (red area in the location index), where flight lines were spaced one eighth of a mile. The lines were flown perpendicular to the flight line intervals of approximately 3 miles except for the Drenchwater Creek area, where the flight interval was 1.5 miles.

An Ashtech G224 NAVSTAR / GLONASS Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a base station of better than 5 m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159° 5' north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m, with respect to the UTM grid.

ELECTROMAGNETICS


To determine the location of EM anomalies or their boundaries, the DIGHEM[®] EM system measured triplate and quadrature components at five frequencies: two vertical coaxial-coil pairs operated at 1000 and 5500 Hz while three horizontal coplanar-coil pairs operated at 800, 7200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. The type of conductor is indicated on the aeromagnetic map by the interpretive symbol attached to each EM anomaly. Determination of the type of conductor is based on EM anomaly shapes of the coaxial- and coplanar-coil responses, together with conductor and magnetic patterns and topography. The power line monitor and the flight track video were examined to locate cultural sources.



TOTAL MAGNETIC FIELD AND DETAILED ELECTROMAGNETIC ANOMALIES OF PARTS OF SOUTHERN NATIONAL PETROLEUM RESERVE - ALASKA, NORTHWEST ALASKA

PARTS of HOWARD PASS B-2 QUADRANGLE


by
Laurel E. Burns, U.S. Bureau of Land Management, Fugro Airborne Surveys Corp.,
and Stevens Exploration Management Corp.
2006



TOTAL MAGNETIC FIELD

The magnetic total field contours were produced using digitally recorded data from a Sinterex cesium CS2 magnetometer, with a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) adjusted for regional variations (or IGRF gradient, 2005, updated to August 2005) using altimeter adjusted IGRF, (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Akima, H., 1970. A new method of interpolation and smooth curve fitting based on local anomalies. *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.



SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Stevens Exploration Management Corp. Airborne geophysical data for the area were acquired and processed by Fugro Airborne Surveys Corp. in 2005. Funding for the project was provided by the U.S. Department of the Interior, Bureau of Land Management (BLM).

This map and other products from this survey are available by mail order in person from DGGS, 3354 College Road, Fairbanks, Alaska, 99709-3707. Published maps are also available for viewing or downloading as Adobe Acrobat Files (.pdf) on our Web site (<http://www.dggs.dnr.state.ak.us/pubs/>). Some products are also available for viewing at the BLM Alaska State Office, 222 W. 7th Avenue, Anchorage, AK 99513.